

Touch Dynamic

QS300

Kiosk



QS300 Kiosk

Options

- Available in 12", 15", 17" and 19" High brightness LCD
- Available with Resistive and SAW touch screen
- Metal bezel, also offered in stainless steel finish
- Available with Celeron M 1.0GHz fanless, Celeron M 1.5GHz or Core 2 Duo 1.66GHz
- Meets 3 1/2" Standard for wall mounting
- Optional Magnetic Strip Reader and/or Biometrics Reader



TOUCH DYNAMIC

IMPROVING TOUCH TECHNOLOGY

Touch Dynamic, Inc • 17 Camptown Road • Irvington, New Jersey 07111
888.508.6824 • www.touchdynamic.com

Touch Dynamic QS300 Kiosk PC Specifications

Model Name	QS392	QS395	QS397	QS399
CPU Support	Celeron M 1.0 fanless / Celeron 1.5GHz / Core 2 Duo 1.66GHz			
Chipset	Intel 852GM FSB 400MHz / ICH4			
System Memory	2 x DDR SO-DIMM Slot up to 2GB			
Graphic Memory	System memory shared up to 96MB			
BIOS	Award			
LCD Touch Panel				
LCD Size	12" TFT	15" TFT	17" TFT	19" TFT
Brightness	370 cd/m	250 cd/m	300 cd/m	300 cd/m
Maximal Resolution	800 x 600	1024 x 768	1280x1024	
Touch Screen Type	Resistive	Resistive (SAW as option)		
Storage				
HDD	1 x 2.5" Slim HDD			
Flash Memory	Compact flash memory option (type I & II)			
Expansion	1 x Mini-PCI			
External I/O				
USB 2.0	4 x USB Type A			
Serial / COM	4 RJ45 Serial Ports			
Parallel	1 x DB 25F			
LAN (10 / 100)	1 x RJ45			
Cash Drawer	1 x RJ11 (12V / 24V)			
1 Locking Power Connector	1 x Latch Type			
Audio Jack	1 x Line-out, 1 x Line-in			
PS2	None	1 PS2		None
2nd VGA	1 DB15	None		1 DB15
Power				
Power Adapter	19V / 90W			
Power				
Speaker	2 x 2 Watt Internal Speakers (None for Ventless Version)			
Environment				
EMC & Safety	FCC Class A / CE Marking / LVD			
Operating Temperature	41°F -104°F			
Storage Temperature	-4°F ~ 140°F			
Operating Humidity	5% ~ 95% RH non-condensing			
Storage Humidity	5% ~ 95% RH non-condensing			
Dust & Water Proof	NEMA 3 / IP 55 (Front Bezel)			
Dimension (WxDxH)	12.5x10.2x2.4"	14.5x11.5x2.4 "	16.2x13.6x2.4 "	17.7x14.7x2.4 "
Weight	10.4lbs	12.8lbs	16.7lbs	19.8lbs
Mounting	100 x 100 mm Standard VESA			
OS	Windows XP, WEPOS, XP Professional for Embedded, Windows 2000 professional Embedded, Linux			



QS300
Rear View



QS300
Ports View